Preliminary investigation of scale formation and fluid chemistry at the Dixie Valley Geothermal Field, Nevada

Carol J. Bruton, Gregory Nimz Lawrence Livermore National Laboratory

Dale Counce, Deborah Bergfeld, Fraser Goff Los Alamos National Laboratory

Stuart D. Johnson Oxbow Power Services, Inc.

Joseph N. Moore Energy and Geoscience Institute

Potential approaches for additional power generation

- Bottoming cycle low-pressure flash
- Supplementing reinjection into the reservoir with local shallow groundwaters to maintain reservoir pressure

Oxbow conducted on-site scaling and mixing tests simulating plant and field conditions which produced variable scaling rates and scale properties


Objectives

- What is the source and composition of scale in injection lines? How can it be controlled?
- Will scale form if reinjection is supplemented with local shallow groundwater to maintain reservoir pressure? Can it be controlled through fluid mixing?
- Will reinjection damage the reservoir over time?


Chemical analyses of major components of test bed scales

Component	Inlet	"Aged"	Exit
Major components (in wt%)			
SiO ₂	62.10	61.56	60.52
Al ₂ O ₃	7.47	6.60	3.84
Fe ₂ O ₃	4.64	3.29	5.82
MnO	0.172	0.197	0.091
MgO	2.88	4.75	10.82
CaO	4.07	3.50	3.64
Na ₂ O	1.19	1.06	1.08
K ₂ O	1.53	1.38	1.02
P ₂ O ₅	0.035	0.031	0.033
CI	0.113	0.058	0.121
F	0.033	0.067	0.183
S	0.136	0.130	0.109
Total organic carbon	0.272	0.172	0.180
Total inorganic carbon	0.083	0.065	0.282

Major element chemistry of LP and injection brines




SiO₂ concentrations in production and injection brines




- Production and injection brines are close to saturation with amorphous silica
- SiO₂(aq) comprises only 58-92% of total silica owing to alkaline pH of brines
- Injection brines are more concentrated than LP brine
- Local shallow groundwater (domestic) is in equilibrium with a, b-cristobalite

Trends in conservative elements show relationships among Dixie Valley fluids



- Mixing/dilution line defined
- Domestic water is mixture of local recharge and approx. 15-25% reservoir fluid

Results of stable isotope measurements



- Reservoir fluids exhibit oxygen isotope enrichment (2-3 %₀₀) owing to rock-fluid interactions
- Recharge seems to occur locally
- Steam loss/mixing relate waters
- Injection waters seem to be slightly more concentrated than LP brine

Results of CI isotope measurements

- ³⁶CI/CI of produced brines and low pressure brine is about 50 x 10⁻¹⁵
- ³⁶CI/CI of local groundwater (167 x 10⁻¹⁵) is higher than brines but lower than regional precipitation (> 320 x 10⁻¹⁵)
- Suggests that local shallow groundwaters are mixture of regional recharge and deeper geothermal brines
- About 12 % of sampled groundwater is geothermal brine, assuming regional recharge has 50 ppm Cl and ³⁶Cl/Cl of 320 x 10⁻¹⁵

Results of d¹³C and ³H isotope measurements


- d¹³C seems to result from mixture of carbonate and organic sources with isotopically enriched and depleted carbon, respectively.
 - $ightharpoonup d^{13}$ C of reservoir fluid and separated CO₂ equals -4.5/ -5.3 0 / $_{00}$, within range of mantle values.
 - > Kennedy et al. (1996) found <10 % of reservoir He is mantle-derived (R/R $_{\Delta}$ 0.7-0.76).
- ³H (tritium) is very low (0.10 T.U.) in reservoir fluids, which suggests minimum mean residence time 75 years and maximum of 10,000 years using piston flow and well-mixed reservoir models, respectively.

Lines of evidence for component of reservoir brine in domestic water

- 36CI/CI results suggest that about 12% of sampled shallow groundwater (domestic water) is geothermal brine
- Mixing/dilution relationships between trace elements and Cl suggest that shallow groundwater contains 15 - 25% geothermal brine
- Shallow groundwater has high HCO₃, SO₄, Ca


Conclusion: Local shallow groundwater contains about 15% geothermal brine mixed with regional recharge

Predicted mineral alteration in present-day geothermal system: Well 76-7



- Quartz is at equilibrium and calcite is slightly supersaturated in reconstructed reservoir fluids from well 76-7.
- Mineralization agrees with Stage VI calcite-quartz veins (Lutz, 1997)
- The alkaline pH of the reservoir brine precludes precipitation of aluminosilicates

Choice of Al concentration controls predicted mineral alteration in present-day geothermal system



Wairakite

Clinozois ite

Quartz


Calcite

Calci

Monomeric AI = 0.041 mg/kg

Total AI = 0.916

Consequences of heating of domestic water



- Carbonates, sulfates and Mgsilicates tend to precipitate
- Silicates such as quartz become increasingly undersaturated

Conclusions

- Local shallow groundwater contains about 15% geothermal brine mixed with regional recharge
- Recharge to the Dixie Valley system seems to occur from local sources
- Scale is dominated by amorphous silica
- The LP brine and injection waters are saturated with amorphous silica, which correlates with the ongoing scaling problem
- Downhole fluids seem to be in equilibrium with calcite and quartz, which is consistent with current mineralization
- Mineral precipitation will likely occur if domestic water is reinjected into the reservoir and/or heated